



1) Active surface 2) Housing 3) Top cover 4) Pot 5) LED function indicator

- NPN
- Normally closed (NC)
- 4.00 mm
- Flush (shielded)
- Connector, M12x1-S04

- switching distance adjustable



IND. CONT. EQ. 81U2  
for use in the secondary of  
a class 2 source of supply



IND. CONT. EQ.  
81U2  
for use in the secondary of  
a class 2 source of supply

**General attributes**

Approvals / Conformity

Basic standard  
Enclosure Type per IEC 60529  
Polarity reversal protected  
Scope of delivery  
Short circuit protected

**Electrical attributes**

Connection type  
Eff. operating current I<sub>e</sub>  
Electrical version  
Operating voltage U<sub>B</sub> max. DC [V]  
Operating voltage U<sub>B</sub> min. DC [V]  
Rated insulation voltage U<sub>i</sub>  
Ripple max. (% of U<sub>e</sub>)  
Sensitivity  
Switching freq. f max. (at U<sub>e</sub>)

CE  
cULus  
IEC 60947-5-2  
IP65  
Yes  
2 nuts  
Yes

Connector  
200 mA  
DC, direct current  
35.0 V  
12.0 V  
75 V DC  
10 %  
switching distance adjustable  
100 Hz

Switching function  
Switching output  
Voltage drop static max.

**Mechanical attributes**  
Ambient temperature T<sub>a</sub> max.  
Ambient temperature T<sub>a</sub> min.  
Connector type  
Cover material  
Diameter d1  
Housing material  
Mech. installation condition  
Mounting length  
Rated operating distance S<sub>n</sub> [mm]  
Sensing face material  
Tightening torque  
Working range S<sub>a</sub> max.  
Working range S<sub>a</sub> min. [mm]

Normally closed (NC)  
NPN  
1.5 V

70 °C  
-30 °C  
M12x1-S04  
PA  
M12x1.0  
1.4301  
Flush (shielded)  
31.0 mm  
4.00 mm  
PTFE  
40 Nm  
4.00 mm  
1.00 mm

