



1) Active surface 2) Housing 3) Top cover 4) Pot 5) LED Power 6) LED function indicator

- NPN
- Normally closed (NC)
- 4.00 mm
- Flush (shielded)
- Cable, PUR, 2.00 m

■ switching distance adjustable



IND. CONT. EQ. 81U2
for use in the secondary of
a class 2 source of supply



IND. CONT. EQ.
81U2
for use in the secondary of
a class 2 source of supply

General attributes

Approvals / Conformity	CE cULus IEC 60947-5-2
Basic standard	IP67
Enclosure Type per IEC 60529	Yes
Function indicator	Yes
Polarity reversal protected	Yes
Power indicator	Yes
Protection Class	II
Scope of delivery	2 nuts
Short circuit protected	Yes
Trademark	GLOBAL

Electrical attributes

Connection type	Cable
Eff. operating current I _e	100 mA
Eff. operating voltage U _e DC	24.0 V
Electrical version	DC, direct current
Max. no-load cur. I _o undamped	15.0 mA
No-load current I _o damped max.	18.0 mA
Operating voltage U _B max. DC [V]	30.0 V
Operating voltage U _B min. DC [V]	10.0 V
Rated insulation voltage U _i	75 V DC
Ripple max. (% of U _e)	10 %
Sensitivity	switching distance adjustable
Switching freq. f max. (at U _e)	100 Hz

Switching function
Switching output
Voltage drop static max.

Normally closed (NC)
NPN
1.5 V

Mechanical attributes

Ambient temperature T _a max.	85 °C
Ambient temperature T _a min.	-25 °C
Cable diameter D max.	3.5 mm
Cable jacket material	PUR
Cable length L [m]	2.00 m
Conductor cross-section	0.14 mm ²
Cover material	PA
Depth	61.0 mm
Diameter d1	M12x1.0
Housing material	PBT
Mech. installation condition	Flush (shielded)
Mounting length	47.0 mm
Number of conductors	3
Rated operating distance S _n [mm]	4.00 mm
Sensing face material	PBT
Storage temperature max.	+85 °C
Storage temperature min.	-25 °C
Tightening torque	1 Nm
Working range S _a max. [mm]	4.00 mm
Working range S _a min. [mm]	1.00 mm

