



1) Active surface 2) Housing 3) Top cover 4) Pot 5) LED function indicator

- PNP
- Normally closed (NC)
- 3.00 mm
- nichtbündig
- Cable, PUR, 2.00 m
- switching distance adjustable



IND. CONT. EQ. 81U2  
for use in the secondary of  
a class 2 source of supply



IND. CONT. EQ.  
81U2  
for use in the secondary of  
a class 2 source of supply

**General attributes**

Approvals / Conformity

Basic standard  
Enclosure Type per IEC 60529  
Polarity reversal protected  
Scope of delivery  
Short circuit protected

**Electrical attributes**

Connection type  
Eff. operating current I<sub>e</sub>  
Electrical version  
Operating voltage U<sub>B</sub> max. DC [V]  
Operating voltage U<sub>B</sub> min. DC [V]  
Rated insulation voltage U<sub>i</sub>  
Ripple max. (% of U<sub>e</sub>)  
Sensitivity  
Switching freq. f max. (at U<sub>e</sub>)  
Switching function

CE  
cULus  
IEC 60947-5-2  
IP65  
Yes  
2 nuts  
Yes

Cable  
50 mA  
DC, direct current  
30.0 V  
11.0 V  
75 V DC  
10 %  
switching distance adjustable  
100 Hz  
Normally closed (NC)

Switching output  
Voltage drop static max.

**Mechanical attributes**

Ambient temperature T<sub>a</sub> max.  
Ambient temperature T<sub>a</sub> min.  
Cable jacket material  
Cable length L [m]  
Conductor cross-section  
Cover material  
Diameter d<sub>1</sub>  
Housing material  
Mech. installation condition  
Mounting length  
Number of conductors  
Rated operating distance S<sub>n</sub> [mm]  
Sensing face material  
Tightening torque  
Working range S<sub>a</sub> max.  
Working range S<sub>a</sub> min. [mm]

PNP  
2.0 V

70 °C  
-10 °C  
PUR  
2.00 m  
0.14 mm<sup>2</sup>  
POM  
M08x1.0  
1.4301  
nichtbündig  
27.0 mm  
3  
3.00 mm  
PTFE  
6 Nm  
3.00 mm  
0.10 mm

