



1) Optical axis receiver 2) Optical axis emitter 3) Sn 4) Output function 5) Stability

- Photoelectric sensor
- Series 5K
- Infrared
- up to 1 m



General attributes

Adjuster	Potentiometer 270° (1x)
Approvals / Conformity	cULus CE
Basic standard	IEC 60947-5-2
Enclosure Type per IEC 60529	IP67
Indicator	Stability - LED GN Output function - LED YE
Polarity reversal protected	yes
Series	Series 5K
Setting	Switching distance (Sn)
Short circuit protected	yes
Trademark	GLOBAL

Electrical attributes

Connection type	Connector
Eff. operating current Ie	100 mA
Eff. operating voltage Ue DC	24.0 V
Electrical version	DC, direct current
No-load current max. Io at Ue	30 mA
Operating voltage UB max. DC [V]	30.0 V
Operating voltage UB min. DC [V]	10.0 V
Ripple max. (% of Ue)	10 %
Switching freq. f max. (at Ue)	500 Hz
Switching function	NO
Switching output	NPN (1x)
Turn on time ton max.	1.00 ms
Voltage drop Ud max. (at Ie)	2.0 V

Mechanical attributes

Ambient temperature Ta max.	55 °C
-----------------------------	-------

Ambient temperature Ta min.	-25 °C
Connector type	M8x1-S49
Detection range Sd	0...900 mm
Eff. operating distance Sr	900 mm
Housing material	PC, PBT
Length 1	10.8 mm
Length 2	19.5 mm
Length 3	43.5 mm
Minimum operating distance	0 mm
Mounting type	Screw M3
Range Sn	Sn = 900 mm, adjustable
Sensing face material	PMMA
Style	Block, 90° connection

Optical attributes

Light type	Infrared
Principle of optical operation	Light scanner, energetic
Switching function, optical	NO: light-on
Wavelength	880 nm

Additional text

Order accessories separately.
For additional information, refer to user's guide.
Only for NFPA 79 applications (machines with a supply voltage of maximum 600 volts).
Device shall be connected only by using any R/C (CYJV2) cord, having suitable ratings.
Reference object (target): Gray card, 200 x 200,

90 % remission, axial approach.
The sensor is functional again after the overload has been eliminated.

Photoelectric sensor

BOS 5K-NS-ID10-S49
BOS015L

BALLUFF

sensors worldwide

