



1) Optical axis receiver 2) Optical axis emitter 3) Output function 4) Sn

- Photoelectric sensor
- Series 5K
- LED, red light
- up to 200 mm



General attributes

Adjuster	Potentiometer 6-turn (1x)
Approvals / Conformity	cULus CE
Basic standard	IEC 60947-5-2
Enclosure Type per IEC 60529	IP67
Indicator	Output function - LED YE
Polarity reversal protected	yes
Series	Series 5K
Setting	Switching distance (Sn)
Short circuit protected	yes

Electrical attributes

Connection type	Cable with connector
Eff. operating current Ie	100 mA
Eff. operating voltage Ue DC	24.0 V
Electrical version	DC, direct current
No-load current max. Io at Ue	30 mA
Operating voltage UB max. DC [V]	30.0 V
Operating voltage UB min. DC [V]	10.0 V
Ripple max. (% of Ue)	8 %
Switching freq. f max. (at Ue)	500 Hz
Switching function	NO
Switching output	PNP (1x)
Turn on time ton max.	1.00 ms
Voltage drop Ud max. (at Ie)	2.0 V

Mechanical attributes

Ambient temperature Ta max.	55 °C
Ambient temperature Ta min.	-25 °C
Cable jacket material	PVC

Cable length	0.10 m
Connector type	M8x1-S75
Detection range Sd	40...200 mm
Eff. operating distance Sr	200 mm
Housing material	PC, PBT
Length 1	10.8 mm
Length 2	19.5 mm
Length 3	26.8 mm
Minimum operating distance	40 mm
Mounting type	Screw M3
Range Sn	Sn = 200 mm, adjustable
Sensing face material	PC
Style	Block, 45° connection

Optical attributes

Light type	LED, red light
Optical special feature	Background suppression
Principle of optical operation	Light scanner, triangulation
Switching function, optical	NO: light-on
Wavelength	660 nm

Additional text

Reference object (target): Gray card, 100 x 100

90 % remission, axial approach.

The sensor is functional again after the overload has been eliminated.

For additional information, refer to user's guide.

Order accessories separately.

Only for NFPA 79 applications (machines with a supply voltage of maximum 600 volts).

Device shall be connected only by using any R/C (CYJV2) cord, having suitable ratings.

